

MSDS - Material Safety Data Sheet**Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON**

MSDS No.: L512

I. Basic Information:**Manufacturer:** RADIATOR SPECIALTY COMPANY**Address:** 600 RADIATOR ROAD**City, ST Zip:** INDIAN TRAIL, NC 28079**Emergency Contact:** Rocky Mountain Poison Control Center**Emergency Telephone Number:** 303-623-5716**Contact:** Robert Geer**Information Telephone Number:** 704-688-3430**Last Update:** 10/04/2006**Chemical State:** Liquid Gas Solid**Chemical Type:** Pure Mixture

1	Health
3	Flammability
0	Reactivity
C	Pers. Protection

II. Ingredients: Trade Secret

CAS No.	Chemical Name	% Range	EHS		IARC		SARA		OSHA PEL	ACGIH TLV	Other Limits
			NTP		SUB Z	313					
10043-11-5	Boron Nitride	0.1 - 5.0							N/D	N/D	
67-63-0	Isopropanol	40.0 - 60.0							400 ppm	400 ppm	
68476-86-8	Liquefied Petroleum Gas	10.0 - 30.0							N/E	1000 ppm	
110-54-3	n-Hexane	30.0 - 60.0					X		50 ppm	50 ppm	
9002-84-0	Polytetrafluoroethylene	0.1 - 5.0							N/D	N/D	

III. Hazardous Identification:**Hazard Category:**
 Acute Chronic Fire Pressure Reactive
Hazardous Identification Information:

Danger: Extremely Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

IV. First Aid Measures:**Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

Chronic: High levels damage the nervous system initially producing a lack of feeling in the extremities and possibly progressing to a more severe nerve damage.

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED.

Medical Conditions Generally Aggravated by Exposure:

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON

MSDS No.: L512

N/D

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: < 0°F

Lower Explosive Limit: N/E

Upper Explosive Limit: N/E

F.P. Method: Calculated

Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread. Use equipment or shielding to protect personnel against venting, rupturing, or bursting containers.

Unusual Fire and Explosion:

Contents under pressure. At elevated temperatures, container may vent, rupture, or burst violently.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Precautions to be Taken:

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

Other Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger extremely flammable.

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON

MSDS No.: L512

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: <100° F

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): > 1.0

Vapor Pressure (mm Hg.): N/D

Specific Gravity (H₂O = 1): 0.67500

Vapor Density (AIR = 1): N/D

Solubility In Water: Insoluble

Appearance and Odor: Clear liquid with white suspended particles with hydrocarbon odor.

Other Information: VOC Content: 94.5%

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Avoid contact with strong oxidizers

Decomposition/By Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON

MSDS No.: L512

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

IMDG

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established

N/D: Not Determined

N/A: Not Applicable

N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.